6HTAA6.5-G22 SDEC Diesel Generator 150kVA Open Type Genset

Basic Information

Place of Origin: CHINA
Brand Name: DELLENT
Certification: CE/ISO9001
Model Number: DE-SC165
Minimum Order Quantity: 1*20GP
Price: face to face

Packaging Details: PLASTIC WRAP OR PLYWOOD CASE
 Delivery Time: 30 DAYS FROM DEPOSIT RECEIVED

Payment Terms: L/C, T/T

• Supply Ability: 500 PCS PER MONTH



Product Specification

Name: SDEC Diesel Generator Open Type

• Engine Model: 6HTAA6.5-G22

Frequency: 50HzEngine Brand: SDEC

• No. Of Cylinder: 6 Cylinder In Line

Rated Speed: 1500rpmVoltage: 400V/230VWarranty: 12 Months

Controller: Deepsea/Smartgen/ ComAp

Prime Power: 120kW/150kVAStandby Power: 132kW/165kVA

Highlight: SDEC Diesel Generator 150kVA,
 SDEC Diesel Generator Onen Tyme

SDEC Diesel Generator Open Type,

150kVA Open Type Genset

6HTAA6.5-G22 SDEC Diesel Engine 150kVA Open Type Genset

. PRODUCT DESCRIPTION

150kVA Standby Power SDEC Genset Soundproof Engine By 6 Cylinder In Line. Dellent Power supply the standby power 150kVA water cooled diesel generator with SDEC brand diesel engine model6HTAA6.5-G22. The water cooled diesel generator with rated output 165kVA /132kW, standby power150kVA /120kW.

- 1. Diesel generators are strong-built, ideal for emergency back-up.job sites and industrial appplications.
- 2. Powered by reliable air/water cooled diesel generators sets, industrial grade, great fuel efficiency, less maintenance, long operating life.
- 3. Strong technology and high-quality personnel, continuous innovation and perfect management.



150kVA Diesel Generator Powered by SDEC Diesel Engine:

Model		DE-SC165	
May Dawer	kVA	165.0	
Max. Power	kW	132.0	
Rate Power	kVA	150.0	
	kW	120.0	
Frequency	Hz	50	
Rate Voltage	V	400/230	
Rate Current	A	216.5	

Specification of the Diesel Engine:

Engine Manufacturer		Shanghai Diesel Engine Co., Ltd.	
Engine Brand		SDEC	
Engine Model		6HTAA6.5-G22	
No. of Cylinder		6 Cylinder in line	
Aspiration		Turbocharged and Air to Air Aftercooled	
Governor		Electric	
Engine Max. Output Power	kW	155	
Displacement	L	6.500	
Starting Voltage	V	24	
Bore	mm	105	
Stroke	mm	124	
Lubrication Oil Capacity	L	15-17.5	
Compression Ratio		16 : 1	
Intake Air Flow	M ³ /Min	N.A	

Fuel Consumption at 100% Load	L	33.1
-------------------------------	---	------

Specification of Automatic Control Panel:

Controller Brand		Deepsea	
Controller Model		DSE6120	
Breaker Brand		Delixi	
Breaker Capacity	A	250	
Battery Charger	Sm	Smartgen Model BAC06A	
Emergency Stop Button		Supply	
Automatic Mains Fail (AMF)		Supply	
Fuel Level		Supply	
Automatic Transfer Switch		ATS as optional part	
Mains Monitor	Suppl	Supply with DELLENT Function	

The control panel supply the full protection with alarm and shutdown of the diesel generator include Start-up fault (generator set shutdown), High coolant temperature (alarm and generator set shutdown), Low oil pressure (alarm and generator set shutdown), Low fuel level (alarm), Low cooling fluid level alarm (as optional), Overload (alarm and generator set shutdown), Battery voltage high (alarm).

Optional controller: Each model of Deepsea, Smartgen, ComAp brand controller.

. Why Choose Us:

Dedicated

We are DEDICATED to meet Customers' need.

Enthusiasm

We respond to our Customers' ENTHUSIASM



We cherish our Customers' LOYALTY



We aim to establish our own LUXURY brand

Efficient

We offer our EFFICIENT service

Newest

We adopt NEWEST technologies for products

rust

We strive for winning the TRUST from Customers

. QUALIFICATION CENTIFICATE:



















. FACTORY INTERIOR:















Fuan Dellent Electric & Machinery Co., Ltd.



+8613706938606





NO.7,JINYE ROADTIEHU INDUSTRIAL AREA CHENGYANG TOWN, FUAN CITY,NINGDECITY,FUJIAN.CHINA